

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

ISSUE CLASSIFICATION	Subclass	Class

PATENT NUMBER

BEST AVAILABLE COPY

U.S. UTILITY Patent Application

<u>WILSON</u>	O.I.P.E.	PATENT DATE
SCANNED <u>10-20-02</u>		<u>mc</u>

APPLICATION NO. 09/496038	CONT/PRIOR YES	CLASS 455	SUBCLASS 12.1	ART UNIT -2749 2746	EXAMINER T. Davis
------------------------------	-------------------	--------------	------------------	---------------------------	----------------------

LICANTS

Satellite broadcasting receiver receiving signal radio waves from two broadcasting satellites

TIME

PTO-2040
12/89

ISSUING CLASSIFICATION

Continued on Issue Slip Inside File Jacket

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input checked="" type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent No. _____ _____ _____	(Assistant Examiner)		(Date)	ISSUE FEE	
	(Primary Examiner)		(Date)	Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of				ISSUE BATCH NUMBER	

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A
(Rev. 1/71)

FILED WITH: DISK (CRF) FICHE CD-ROM

(Attached in pocket on right inside flap)